Data sheet - product specifications







Name: **RB** Range

Properties: Heavy duty contract range

Style: Floor and desk screen dividers

Top styles: Flat, wave and radius Types: Flat, curved & visions Designed for: High demand work areas

Bespoke sizes: Special sizes and shapes made to order.

DT clamp range, DT2 as standard, 8 other types are available. Clamp brackets:

Core frame: P2 particle board.

MDF medium density fibre board, 100% recyclable material & Core panels:

environmentally sustainable.

ECO content: An average of 92% of the screens content is recyclable. Edges: Linking or non-linking are UPVc edges & fabric edges to order. Fabrics: Stock fabric Elfin, all Camira and other fabrics available to order. BS 476, Part 7, Class 1 or BS5852 Class 0, 1, or BS 7176:2007 Fabric flammability:

depending on the fabric, environment and substrate.

Feet floor standing: STD stabilising feet supplied as standard, other styles available.

Feet linking: ALF supplied as standard, other styles available.

Foam: Combustion Modified to comply with Schedule 1 Part 1 of the

Furniture & Furnishings (Fire Safety) Regulations S.I. 1324 1989.

Guarantee: 5 Years.

Height allowance: Desk top screens are 8mm less than stated to allow for the

thickness of the clamps.

Height: The screen height is measured from corner to corner

Heights desk divider: 30cm, 40cm & 50cm.

Heights floor divider: 120cm, 150cm, 165cm & 180cm.

Height allowance: The height tolerance is plus or minus 0.5%.

Packing for ECO vans: Packed with cardboard corners and heavy polythene wrap.

Packed as required, extra costs may apply. Packing for carriers:

Thickness: Overall thickness 30mm.

Deliveries are by ECO's vehicles to the customer's requested Transportation:

postcode subject to being within ECO's delivery area map.

The width tolerance is plus or minus 0.5%. Width allowance:

Widths desk divider: 80cm, 100cm, 120cm, 140cm, 150cm, 160cm & 180cm.

Widths floor divider: 80cm, 100cm, 120cm, 140cm, 150cm & 160cm.







